

## Hi-F0420FBL

Product	4+2 Port 250m POE Switch (External)
Model	Hi-F0420FBL
POE Port	1 to 4 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+、 3/6- and 4/5+7/8-
Whole Power	≤78W (52V 1.5A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3、 IEEE802.3u、 802.3x、 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	1.6Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps 1000Mbps:14800pps
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps;POE Status Indicator; Power indicator;Extender
Working Environment	Working temperature: -10°-- 55°C
Weight	1kg
Size	200mm*120mm*40mm(L*W*H)