

Hi-F1621GBL

| | |
|---------------------|---|
| Product | 16+2+1 port 250m POE switch(Built-in) |
| Model No. | Hi-F1621GBL |
| PoE Port | 1 to 16 port support IEEE802.3af/at |
| UP link port | 17 th -18 th port support 1000Mbps |
| PoE output | 15.4W/30W IEEE802.3af/at |
| PoE whole power | ≤250W |
| PoE type | End-span |
| Power distance | ≤250m |
| Network Standard | IEEE 802.3、IEEE802.3u、802.3x、802.3af/at |
| Network Medium | 100/1000BASE-TX: 5 class and above non shielded twisted pair |
| Data Distance | ≤250m |
| Switch capability | 12Gbps |
| Forwarding Mode | Store and forward |
| Forwarding Rate | 100Mbps:14880pps 1000Mbps:14800pps 1000BASE-T: 1488095pps/port |
| MAC Address | 2K MAC address table |
| Port function | Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode |
| Indicator | LINK/ACT. 100Mbps;POE Status indicator; POWER indicator;EXTENDER indicator |
| Working Environment | Working Temperature: -10°-- 55°C |
| Input power | AC100-240V 50/60HZ |
| Weight | 2.1kg |
| Size | 270mm*180mm*44mm(L*W*H) |